

PC-1

Technical Data Sheet



SYMBOL	pН
DP-26	8

Very easy-to-use paint protection based on quartz, carnauba wax and PTFE. It perfectly repels water and gives extra gloss, also enhances paintworks colour depth whilst protecting from dirt settlement. PC-1 can be used as a reloader for ceramic paint coatings.

APPLICATION:

- car body, car paint

COMPOSITION:

- < 20% alcohol

- < 5% non-ionic surfactants

- auxiliary substances

USAGE:

Product is ready to use without diluting.

Apply to a clean and dry surface. Spread it evenly over the surface using an applicator then buff gently with a soft towel. Use another soft towel to buff paintwork to a shine finish. Avoid application to hot surface.

Warning: Do not use in full sun, or on the heated surfaces.

CLASSIFICATION OF THE MIXTURE:

tel. +48 91 311 97 77 fax. +48 91 311 97 79

E-mail: info@tenzi.pl, www.tenziprodetailing.com



PC-1

Technical Data Sheet



Signal words:

DANGER

Hazard statements:

H226 – Flammable liquid and vapour.

Precautionary statements:

P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

SELL-BY DATE:

36 months from the production date.

Production date/series and expiration date are stated on the packaging.

ADDITIONAL INFORMATION:

Additional information can be found in safety data sheet.

Contaminated containers should be completely emptied. Several times rinse the container promptly after emptying. Empty container can be stored in containers for collection of plastic packaging, or can be delivered to specialized company for recycling.

Disposal should be in accordance with the national/international regulations

tel. +48 91 311 97 77 fax. +48 91 311 97 79

E-mail: info@tenzi.pl, www.tenziprodetailing.com