


R1 RIM

Technical Data Sheet



Nano-ceramic coating for rims. Dedicated for chrome, aluminum and paint-coated rims. Super hydrophobic effect and protection from water, salt, dust and UV-rays. Increased protection against scratches.

APPLICATION:

- wheel rims

COMPOSITION:

- < 40% alcohols
- < 40% hydrocarbons C₉₋₁₁
- < 30% silicates
- auxiliary components.

USAGE:

Product is ready to use without diluting.

Perform the whole operation in 18-24°C (in closed room for the best effect). Make sure the rim is clean and cool. Degrease and remove old coatings from rims before application. Wrap small cloth around soft-side of the applicator. Apply few drops of R1 Rim onto applicator covered with small cloth. Apply thin and even layer onto rim. Leave the layer on the surface for approx. 7-8 minutes (bonding time). Buff the surface with big microfiber towel to a high gloss. Apply additional layers with minimum time interval of 3 hours (3 layers recommended). Drying time after application of last layer - 8 hours.

Do not apply R1 Rim to hot surfaces or in direct sunlight.



R1 RIM

Technical Data Sheet

CLASSIFICATION OF THE MIXTURE:



Signal words: DANGER

Hazard statements:

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- **H336** May cause drowsiness or dizziness.

Precautionary statements:

P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 – Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

P405 – Store locked up.

SELL-BY DATE:

36 months from the production date.

Production date/series and expiration date are stated on the packaging.

ADDITIONAL INFORMATION:

Additional information can be found in safety data sheet.

Contaminated containers should be completely emptied. Several times rinse the container promptly after emptying. Empty container can be stored in containers for



R1 RIM

Technical Data Sheet

collection of plastic packaging, or can be delivered to specialized company for recycling.

Disposal should be in accordance with the national/international regulations